



CLS - Surface Mounted - Focus Spot

Main features:

EN

An extensive cooperation with leading lighting designers in the museum world has resulted in a revolutionary range of display lighting for museums, galleries and retail applications. Never before have lighting designers had such a powerful tool at their disposal for optimum showcase lighting:

The CLS zoom system enables lighting designers to vary the beam angle between 15° and 65°.

Choice of [typical] 85 and 95 CRI versions for optimum colour reproduction.

Internal slot for colour correction filters.

Large horizontal and vertical adjustability, for optimum positioning flexibility.

Optional extension rods of 10 & 30 cm height, for variable heights of the pole.

Maximum power consumption 3 Watt.

Dimmable via 1-10V, DMX or mains (phase cut).

NL

De ultieme lichtoplossing voor vitrine toepassing in musea, galeries en winkels waar een compact armatuur is gewenst met een aantal unieke specificaties:

Het CLS zoom systeem stelt lichtontwerpers in staat om de openingshoek van het licht variabel in te stellen tussen de 15° tot 65°.

Keuze uit CRI waarde van typical 85 of 95 CRI voor optimale kleurweergave.



Intern slot voor het aanbrengen van correctie of kleurfilters.

Grote horizontale en verticale verstelbaarheid van het armatuur voor optimaal richten van de spots.

Door middel van optionele 10 cm & 30 cm lange montage stelen is de focus tot 140 cm in hoogte te verstellen.

Maximaal opgenomen vermogen slechts 3 Watt.

Dimbaar middels 1-10V, fase dimbaar of DMX 512 signaal.



Products Focus Spot series:

- F-1-2-01-Z
- F-1-2-02-Z
- F-1-2-03-Z
- F-1-2-04-Z
- Y106000
- Y106002



- CLS Focus 2700K, zoom, black, 85 CRI
- CLS Focus 3000K, zoom, black, 95 CRI
- CLS Focus 3000K, zoom, black, 85 CRI
- CLS Focus 4000K, zoom, black, 85 CRI
- CLS Focus extension pipe 10 cm, black
- CLS Focus extension pipe 30 cm, black

