




COVELIGHT SUPERIOR 5M


LEDs:	3 in 1 SMD
Available colours:	Warm white 3000K
Available lenses:	--
Input voltage:	24 VDC
Power consumption:	Max. 6 W/m
Housing:	Silicone gel
IP value:	IP44
Measurements:	14 x 4 mm (hwx)
Weight:	80 gr/m





COVELIGHT SUPERIOR 5M


LEDs:	3 in 1 SMD
Available colours:	Warm white 2700K
Available lenses:	--
Input voltage:	24 VDC
Power consumption:	Max. 9 W/m
Housing:	Silicone gel
IP value:	IP44
Measurements:	14 x 4 mm (hwx)
Weight:	80 gr/m






COVELIGHT SUPERIOR 10M


LEDs:	3 in 1 SMD
Available colours:	Warm white 3000K
Available lenses:	--
Input voltage:	24 VDC
Power consumption:	Max. 6 W/m
Housing:	Silicone gel
IP value:	IP44
Measurements:	14 x 4 mm (hwx)
Weight:	80 gr/m



PRODUCTS



140095 / 141000



140080



141006

140095	CLS Covelight Superior warm white 3000K 24VDC 5mtr
140080	CLS Covelight Superior warm white 2700K 24VDC 5mtr
141000	CLS Covelight Superior warm white 3000K 24VDC 10mtr
141006	CLS Covelight Superior plastic mounting profile, 2 metres

ACCESSORIES



707011



707012



707037



872012

706995	CLS BT20.24 LED power supply 24VDC 20VA 85-264VAC
707011	CLS BT45.24 LED power supply 24VDC 45VA 85-264VAC
707012	CLS BT75.24 LED power supply 24VDC 75VA 85-264VAC
707013	CLS BT120.24 LED power supply 24VDC 120VA 85-264VAC
707014	CLS BT240.24 LED power supply 24VDC 240VA 85-264VAC
707037	CLS LDV-45 DMX LED dimmer, 4 channels 5Amp 12V-48V output
872012	CLS Dimmer Covelight 10-100% input 10-30V output 12V/140W or 24V/280W
871609	Anti static wristband

--- COVELIGHT SUPERIOR ---

PRELIMANARY



Office, The Netherlands

CLS™ COVELIGHT SUPERIOR

CLS offers the ultimate cove lighting product for warm white lighting. With this colour temperature it offers a warm type of light that will be appreciated by users worldwide.

Covelight Superior has the following unique specifications:

- Covelight Superior uses 3 in 1 high quality SMD chips and is therefore the brightest flexible tape product on the market!
- Covelight Superior is delivered on 10 and 5 meter rolls. 1 power line can already feed 10 meters. So a cove of 20 meters length only takes a single power supply; the installer can place a power supply in the middle.
- Covelight Superior uses a silicone protection cover to make the product waterproof. All other products on the market now use a PVC cover. PVC is a few percent brighter when installed, but already

after 500 – 1,000 hours the PVC cover turns brown, taking away up to 50% of the light output.

- Very easy to install since the connection wires are already fixed on the product. For fast mounting, 3M tape is standard on the product. To extra secure the product on certain surfaces, mounting clips are included in the accessory kit.
- A cutting length of ± 20 cm or ± 16,5 cm. (check the cutting marks on the LED line, indicated by a sissor).

Not only for cove lighting is our Covelight Superior the first choice. Also in all sorts of furniture applications the cove light will be a perfect solution.