



Main features:

EN

15,4 Watt module can replace a 100 Watt halogen source, 36 Watt TC-L, 35 Watt HQI.

High quality easy interchangeable lens optics in different beam angles; 25°, 40°, 60° and 120°.

Massive aluminum CNC cut housing for optimal cooling.

Optional diffusion filter for very soft light dispersion available.

Each module is horizontally and vertically adjustable.

Round-, square-, dual- and triple mounting plate available.

Dimming possible.

CLS SmartConnect system.

NL

Met een vermogen van slechts 15,4 Watt kunnen talloze lichtbronnen zoals Halogeen 100 Watt, 36 Watt TC-L en 35 Watt HQI vervangen worden.

Keuze uit 25°, 40°, 60° en 120° licht openingshoek.

CNC gefreesde massief aluminium behuizing voor optimale koeling.

Optioneel een soft tone diffusie filter verkrijgbaar.

Horizontaal en verticaal verstelbaar.

Ronde-, vierkante-, tweevoudige- en drievoudige rechthoekige montageplaat.

Dimbaar.

CLS SmartConnect systeem.



Products Luxo 6 series:

L-6-1-02-2



CLS Luxo 6, module, medium flood 40°, 6 x Cree/Luxeon neutral white 4000K, IP40, size ø 126 x 60 mm (øxh)

L-6-1-03-2



CLS Luxo 6, module, medium flood 40°, 6 x Cree/Luxeon warm white 3000K, IP40, size ø 126 x 60 mm (øxh)

L-6-1-04-2



CLS Luxo 6, module, medium flood 40°, 6 x Cree/Luxeon extra warm white 2700K, IP40, size ø 126 x 60 mm (øxh)

Y111611



CLS Luxo 6 round ceiling unit alu-brushed 1 hole, size ø 145 x 42 mm (øxh)

Y111621



CLS Luxo 6 square ceiling unit alu-brushed 1 hole, size 42 x 145 x 145 mm (hxwd)

Y111632



CLS Luxo 6 rectangular ceiling unit alu-brushed 2 holes, size 42 x 290 x 145 mm (hxwd)

Y111633





CLS Luxo 6 rectangular ceiling unit alu-brushed 3 holes, size 42 x 430 x 145 mm (hxwd)

Y111690



CLS Soft diffusion filter for Luxo 6



| | | | | | | | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |